



THE RIGHT SPECS. THE RIGHT FEATURES. THE RIGHT SUPPORT.





SE300 SERIES SMART SWITCHES

BRIDGING THE GAP BETWEEN UNMANAGED AND MANAGED SWITCHES

SE300 Series smart switches deliver basic management capabilities at a fraction of the cost of a fully managed switch. Why pay for additional features if they are irrelevant to your application?

SE300 Series smart switches can be used in two ways. (1) They can be deployed as plug and play unmanaged switches right out of the box. (2) Using iView² or the eWorx Utility gives them basic management capabilities as well. The switches support Modbus/TCP to communicate with SCADA software and SNMP to communicate with NMS (Networking Management System) at the same time. This gives full read control to both control engineers and IT.

Limited Lifetime Warranty

Essential Management Features

SE300 switches provide SNMP and Modbus/ TCP management capabilities.

Intelligent Inside

- IEEE 802.1p QoS (Zero Touch)
- Jumbo frame support -- 9,216 bytes
- Free Management Tool IView²
- Loop Detection
- Full Gigabit with PoE/PoE+ options
- Fully Compatible with the Most Popular SCADA/HMI Software
- IP address assignment, allowing for a static IP address or an address that is discoverable via DHCP

HMI/SCADA Software Integration


- System Information
- Device Status/IP Address
- Port Information
- Port Status/Port Speed
- Packet Information
- Tx/Rx Error Packets

Dual Power Inputs - 8.4 to 52.8 VDC

- Overload current protection
- Power-fail Relay

Designed and Built for Hazardous Environments

- Wide Temp design, -40 to 75C
- MTBF: Over 590 years
- Radiated/Conducted noise protection, EMC Level 3





Ethernet Green®, IEEE802.3az Energy-Efficient Ethernet

- eWorx Switches cut power usage by up to 60%, reducing total cost of ownership
- Automatically powers down ports that have no link
- Budgets power output for different Ethernet cable lengths

Wide Variety of Port Configurations

- 5 Ports, up to 18 Ports
- 10/100Mbps & Gigabit models
- Fiber module options (M.M, S.M)
- Fiber connector options (SC,LC,ST)

Industrial Certifications Tailored to Meet the Needs of Your Application


- IECEx
- UL508
- Class I, Division 2 Group A,B,C, D
- ATEX Zone 2

Models with PoE/PoE+ Option

- IEEE802.3af/at compliant
- Each port, up to 30 W
- PoE power budget, Max. 60 W

- Smart PoE management

IT/OT CONVERGENCE



IT Networking Software SNMP





ENABLING INNOVATION

- · Reduced direct costs for installation and deployment
- Reduced power consumption
- Faster developmenmt and deployment cycles with lower project risk
- · Protection of initial investment as system requirements change
- Integrate new technologies as they emerge
- Maximizes lifetime Return On Investment

Distributor:

B+B SMARTWORX

Powered by

ADVANTECH

Worldwide Headquarters

ADVANTECH No.1, Alley20, Lane26, Rueiguang Road Neihu District, Taipei 11491 Taiwan, R.O.C Phone: 0800-777-111 www.advantech.com

European Headquarters

Oranmore, Co. Galway, Ireland Phone: +353 91 792444 Fax: +353 91 792445 eSales@advantech-bb.com

Corporate Headquarters

707 Dayton Road Ottawa, IL 61350 USA Phone: 1-815-433-5100 Fax: 1-815-433-5109 orders@advantech-bb.com www.advantech-bb.com

Middle East, UAE, Africa

Alaa Dalghan, General Manager adalghan@advantech-bb.com Mobile: +971 50 943 65 62 AG Silver Tower, JLT, P.O. Box 48777 Dubai, UAE

Conel s.r.o

Sokolská 71, 562 04 Ústí nad Orlicí III. Czech Republic Phone: +420 465 521 020 Fax: +420 464 647 299 GSM: +420 603 872 287 sales@conel.cz

Latin America, Carribean

Fanny Scargle fscargle@www.advantech-bb.com Phone: 1-727-797-0300 Cell: 1-727-480-5920 Skype: fscargle

OEM & Product Modification

Phone: 815-433-5222 Fax: 815-433-5104 Attn: Custom Dept. custom@advantech-bb.com Custom Quote Request Form: http://advantech-bb.com/custom